


Performance Curve Data Sheet

Customer/Company Name:	ASP Representative:
Contact Name:	
	Rep. Phone:
	Rep. Fax:
Application:	
Product Being Pumped:	
Product Specific Gravity:	Pump Catalog No:
	deg. F/deg. C Motor Horsepower:
	ctp./cts./SSU_Pump BHP @ Point:
	gpm Pump BHP @ Run Out:
Head Rating Point:	feet/psig Mechanical Seal:
	psig Special Features:
90 Imp/Case Clearance A: 0 - 5 mil clear B: 8 - 12 mil clear C: 15-20 mil clear D: 25-30 mil clear	SSP Performance 70 260 Vane - 3500 RPM 60
70 A	HP 1.50 HP 50
Lead ft for the second	40
а 50 50	30
40	20
30 Model: SSP Size: 1SP Ports: 1.0"x1.25" NPT Imp. Dia: 4.38"	10 Motor horsepower
Vane = 0.260 RPM = 3500 20	lines do not include motor service factor.
0 10 20 30	40 50 60 70 80 Capacity - gal./min.

Clean water based performance at 60 deg. F.



14032 South Avalon Blvd. Los Angeles, CA 90061 Phone (310) 630-8089 ~ Fax (310) 630-8095